

TTIC 31250 An Introduction to the Theory of Machine Learning

Homework # 1

Due: April 6, 2022

Groundrules:

- Homeworks will generally consist of *exercises*, easier problems designed to give you practice, and *problems*, that may be harder, and/or somewhat open-ended. You should do the exercises by yourself, but you may work with 1-2 friends on the problems if you want. (Working together doesn't mean "splitting up the problems" though.) If you work with a friend, then *write down who you are working with*.
- If you've seen a problem before (sometimes I'll give problems that are "famous"), then say that in your solution. It won't affect your score, I just want to know. Also, if you use any sources other than material handed out, write that down too. It's fine to look up a complicated sum or inequality, but don't look up an entire solution.

Exercises:

1. **Grading Signup.** Please sign up to grade one of the homeworks using this Google Form.
2. **Expressivity of LTFs.** Recall that a decision list is an if-then-else... function where each if-condition examines the value of a single variable, e.g., "if $x_4 = 0$ then $+$ else if $x_7 = 1$ then $-$ else ...". It is easy to see that conjunctions (like $x_1 \wedge \bar{x}_2 \wedge x_3$) and disjunctions (like $x_1 \vee \bar{x}_2 \vee x_3$) are special cases of decisions lists. Show that decisions lists are a special case of linear threshold functions. That is, any function that can be expressed as a decision list can also be expressed as a linear threshold function " $f(x) = +$ iff $w_1x_1 + \dots w_nx_n \geq w_0$ ".
3. **Decision tree rank.** The *rank* of a decision tree is defined as follows. If the tree is a single leaf then the rank is 0. Otherwise, let r_L and r_R be the ranks of the left and right subtrees of the root, respectively. If $r_L = r_R$ then the rank of the tree is $r_L + 1$. Otherwise, the rank is the maximum of r_L and r_R .

Prove that a decision tree with ℓ leaves has rank at most $\log_2(\ell)$.

Problems:

4. **Decision List mistake bound.** Give an algorithm that learns the class of decision lists in the mistake-bound model, with mistake bound $O(nL)$ where n is the number of variables and L is the length of the shortest decision list consistent with the data. The algorithm should run in polynomial time per example. Briefly explain how your algorithm can be extended to learn the class of k -decision lists with mistake bound

$O(n^k L)$, where a k -decision list is a decision list in which each test is over a conjunction of k variables rather than just over a single variable.

Hint: think of using some kind of “lazy” version of decision lists as hypotheses.

5. **Expressivity of decision lists, contd.** Show that the class of rank- k decision trees is a subclass of k -decision lists. (There are several different ways of proving this.)

Thus, we conclude that we can learn constant rank decision trees in polynomial time, and using Exercise 3 we can learn arbitrary decision trees of size s in time and number of examples $n^{O(\log s)}$. (So this is “almost” a PAC-learning algorithm for decision trees.) Note that the algorithm is not “proper” because it does not output a decision tree.